

# SLP180S-24U

## High Efficiency Monocrystalline PV Module


- Nominal 24V DC for standard output.
- Outstanding low-light performance.
- Heavy-duty anodized frames.
- High transparent low-iron, tempered glass.
- Designed to withstand high wind pressures, hail and heavy snow.
- Quality aesthetic appearance.

**60 CELL**  
MONOCRYSTALLINE MODULE

**180W**  
POWER OUTPUT

**20.00%**  
MODULE EFFICIENCY

**5%**  
POSITIVE TOLERANCE



**High Efficiency**

Module Efficiency improved through advanced cell technology and manufacturing capabilities



**High PID Resistance**

Advanced cell technology and qualified materials lead to high resistance to PID




**Withstands Harsh Environment**

High PID resistance  
5400 Pa positive load  
2400 Pa negative load  
Salt mist (IEC 61701)


### Performance Warranty

**10** years  
Product Warranty

**25** years  
Power Warranty





Positive mechanical load >5400Pa  
Positive Power Tolerance 0~+5W  
Warranty Information 2 Year Product Warranty and Workmanship




Electrical Characteristics	SLP180S-24U
Product code	180032401A
Maximum power (Pmax)	180W
Voltage at Pmax (Vmp)	34.74V
Current at Pmax (Imp)	5.19A
Open-circuit voltage (Voc)	40.07V
Short-circuit current (Isc)	5.47A
Temperature coefficient of Voc	-(80±10)mV/°C
Temperature coefficient of Isc	(0.065±0.015)%/°C
Temperature coefficient of power	-(0.5±0.05)%/°C
NOCT (Air 20°C; Sun 0.8kW/m² wind 1m/s)	47±2°C
Operating temperature	-40°C to 85°C
Maximum system voltage	1000V DC
Power tolerance	± 5%

\*STC: Irradiance 1000W/m², AM1.5 spectrum, module temperature 25°C  
\*NOCT: Nominal operating cell temperature (the data is only for reference)

Specifications	SLP180S-24U
Cells	Monocrystalline silicon solar cell
No. of cells and connections	60(4X15)
Module dimension	1320mm[51.97in.]x705mm[27.76in.]x35mm[1.38in.]
Weight	10.32kg[22.75lbs]
Packing information(Carton)	1370mm[53.94in.]x755mm[29.72in.]x85mm[3.35in.]/(1pc/ctn)




Junction Box  
Top View (Lid Open)



Section A-A

Characteristics



SLP180S-24U I-V Curves

Dimensions in brackets are in inches.  
Un-bracketed dimensions are in millimeters.  
Unit: mm[in.]